

SiTrack:One

Precision and Flexibility

精确，灵活

Stuart Woods

HxGN Live China 2018, Beijing, China - China National Convention Center
11th of September

2018年海克斯康北京用户大会



HEXAGON

Leica
Geosystems

SiTrack:One

Application areas

应用领域



Position Independent
Underground or above

无惧环境
地铁、露天铁路均可

Fast As-built Rail 3D Capture
Deliverables 100% in/from point cloud

快速获取竣工数据
成果100%源于点云

Safety
Designed to reduce foot traffic on rail, **no stop/go**

安全
基于减少步行的设计
无需走走停停

High Accuracy
onsite calibration, inertial systems at 1000 Hz, rail profiling by HD scanner

高精度
现场自检，
1000Hz 惯导系统，
高分辨轨道表面扫描仪



HEXAGON

Leica
Geosystems

SiTrack:One

Scanner-Option Leica P40

徕卡P40三维激光扫描仪



- Customers in Europe, Asia and Latin America
- Leica P40 field of view : 330°
- Rotation frequency: 50Hz – 100Hz
- Recommended measurement speed: 1m/s

客户覆盖亚洲，欧洲，南美
P40视场角：330°
扫描频率：50-100Hz
建议采集速度：1m/s



Measurement in UK
英国测量现场照片

Scan-Data from tunnel-measurement

隧道扫描点云数据



HEXAGON

Leica
Geosystems

SiTrack:One

Scanner-Option Profiler (ZF 9012) 断面仪配置版

- Customer intermetric GmbH in Germany
- Recommended measurement speed: 1m/s
- Profiler 9012 field of view: 360°;
- Rotation frequency: 50Hz – 200Hz

德国用户

建议采集速度：1m/s

断面仪视场角：360°

扫描频率：50-200Hz



Example Munich-underground - Station “Olympia shopping centre”

应用案例—慕尼黑奥林匹克购物中心地铁站



Example Munich-underground – Scan-Data

慕尼黑地铁站扫描点云图



Platform gauging

站台测量

Tunnel measurement


隧道扫描



SiTrack:One

Workflow - Preparation On-site measuring of Control Points


作业流程 – 控制点准备



SiTrack:One

Workflow - On-site Calibration

作业流程 – 现场自检校



Self Calibrating Spheres System
靶球自检校系统

SiTrack:One

Types of measurement and processing 测量流程

■ 4 different options of processing measurement data:

➤ With GCP for underground, tunnels and open sky

- Constrained – 360° start/stop scan → Leica P40
- Constrained – start/stop total station → Profiler 9012
- Minimal constrained → P40 and 9012

➤ Without GCP for open sky only

- GPS based → P40 and 9012

• 4种不同的作业流程

• 有控制点，地铁隧道/露天铁路

- 约束 – 起止点静态360° 扫描法 – 徕卡P40扫描仪
- 约束 – 起止点全站仪定位法 – 断面仪版
- 最小约束法 – 徕卡P40扫描仪或断面仪

• 无控制点，露天铁路

- 基于GNSS定位 – 徕卡P40扫描仪或断面仪



SiTrack:One

Measuring options and their benefits

- Constrained – 360° scan:
 - High accuracy from the very beginning of the movement to the stop
 - Average accuracy for a GCP distance between 50m - 80m
 - Average accuracy for a GCP distance between 60m - 150m
- Constrained – total station:
 - High accuracy from the very beginning of the movement to the stop
 - Average accuracy for a GCP distance between 50m - 80m
 - Average accuracy for a GCP distance between 60m - 150m
- Minimal constrained:
 - High accuracy from the first GCP to the last GCP
 - For start/stop position no GCP-box or total station needed
 - Needs calibration section before 1st GCP/ after last GCP
- GPS based:
 - GPS accuracy from very beginning of the movement to the stop
 - No total station needed / no GCP needed

测量方式与优势

→ P40

→ $\Delta XY < 5\text{mm}$; $\Delta Z < 5\text{mm}$

→ $\Delta XY < 1\text{cm}$; $\Delta Z < 1\text{cm}$

→ Profiler 9012

→ $\Delta XY < 5\text{mm}$; $\Delta Z < 5\text{mm}$

→ $\Delta XY < 1\text{cm}$; $\Delta Z < 1\text{cm}$

→ P40 and Profiler 9012

→ Time saving

→ Calibration section: 10m - 30m

→ P40 and Profiler 9012

→ Fast and easy

约束 – 起止点360° 静态扫描法:

- 起止点之间精度高 – P40
- 每50-80米一个控制点的平均精度: $\Delta XY < 5\text{mm}$; $\Delta Z < 5\text{mm}$
- 每60-150米一个控制点的平均精度: $\Delta XY < 1\text{cm}$; $\Delta Z < 1\text{cm}$

约束 – 全站仪法:

- 起止点之间精度高 – 断面仪
- 每50-80米一个控制点的平均精度: $\Delta XY < 5\text{mm}$; $\Delta Z < 5\text{mm}$
- 每60-150米一个控制点的平均精度: $\Delta XY < 1\text{cm}$; $\Delta Z < 1\text{cm}$

最小约束法:

- 从第一个到最后一个控制点之间精度高 – P40和断面仪
- 起止位置无需控制点或全站仪 – 节省时间
- 在第一个控制点前、最后一个控制点后, 需要10-30米检校距离

基于GNSS定位法:


- GNSS精度 – P40或断面仪
- 无需全站仪或控制点 – 快速简单



SiTrack:One

Workflow - 3D Capture - Using GNSS and/or Control Points


作业流程 – 采集 – 基于GNSS定位 或 控制点



SiTrack:One

SiSynchro - Synchronization of Scan-Data - Basic workflow


SiSynchro预处理软件



SiTrack:One


SiSynchro – Option constrained – 360° start/stop scan

SiSynchro起止点静态扫描约束法




SiTrack:One

SiSynchro – Option constrained – total station SiSynchro起止点全站仪约束法




SiTrack:One

SiSynchro – Option minimal constrained 最小约束法



SiTrack:One

SiSynchro – Option GPS based (only open sky): 基于GNSS定位法




SiSynchro – Accuracy of control-points – GCP every 50m - 80m

Bsp.	<	5mm
Bsp.	<	1cm
Bsp.	<	2cm
Bsp.	>	2cm

SiTrack:One

SiSynchro – Accuracy of control-points - GCP every 60m – 150m


控制点间隔：60-150米，精度



SiTrack:One

SiSynchro - Accuracy of control-points - GCP every 60m - 150m

控制点间隔：60-150米，精度






SiTrack:One

Railway Tasks - Boundary-Conditions

铁路检测任务



- To provide high absolute accuracy: Control-Points (CP) needed
- Boundary-Condition to reach desired absolute accuracy: **CP-Spacing**
- Boundary-Condition to **realize desired Railway-Task**: **CP-Spacing**

- 提供高精度绝对坐标：需要控制点
- 满足绝对精度要求：取决于控制点间距
- 实现任务要求：控制点间距



SiTrack:One: control point
accessory box

SiTrackOne靶球附件箱



HEXAGON



SiTrack:One

Railway Tasks - Accuracy Table

铁路检测任务 – 精度表

Comparison of Usage-Cases 对比应用案例


railway task / usage case	Rules DB-AG	Rules DB-AG	SiTrack:One	
	Absolute accuracy 3D	Relative accuracy/10m	Possibility	CP* - Spacing
clearance typical (SNCF, DB-AG-LimezIII) - maintenance	25mm	<10mm	x	150-1000m
clearance new DB (new construction, f. ex. platforms)	5mm	3mm	x	30m
Distance to neighborhood/adjacent track	15mm	7mm	x	100m
Catenary/Electric wires	15mm	7mm	x	100m
Track geometry - maintenance	20mm	5mm	x	100m
Track gauge/cant from Pt CId** (maintenance)	15mm	2mm***	x	100m
Track gauge/cant from Pt CId** (new construction)	3mm	1mm***	x	30m
Track geometry - new construction highspeed (Acceptance meas.)	7mm	2mm	x	30m
Bridge-sleeper-replacement	4mm	2mm	x	20m
Rail-Wear-Calculation	-	1mm	x	-
clearance measurement				CP... Control Point
geodetic measurement				
high accurate geodetic measurement				****baseline length between reference stations < 10km
				*****depending on tunnel-length
*a priori absolute accuracy CP-points: Necessary absolute accuracy CP-points (from network adjustment) depends on railway-task				
**Accuracy reachable by special post-processing algorithms				
***SiTrack:One: Track gauge from additional gauge-measurement-system with relative accuracy up to 0.3mm possible				



SiTrack:One

Railway Tasks – New Feature - Rail-Wear-Calculation

铁路检测任务 – 计算轨面磨损





- High frequency point cloud of rail
- Rail profile scanners – high-end technology (1000Hz)
- Automated export of rail informations

- 高频率扫描点云
- 轨道表面扫描仪：高端技术（1000Hz）
- 自动导出钢轨表面信息

Configuration 配置:


- 2 Scanner Heads 双头
- 4 Scanner Heads 四头




SiRail-Suite

Software Packages

配套软件包



SiRail Essential (Plus)



ATrack

Everyone		Professionals
Essential 必配版	Essential Plus 高级版	Advanced 完整版
SiRailScan - Basic configuration - Batch rail extraction - Semi-auto rail extraction - Batch catenary detection - Batch clearance static gauge	SiRailScan - Basic configuration - Batch rail extraction - Semi-auto rail extraction - Batch catenary detection - Batch clearance static gauge - Batch tunnel deformation - Batch clearance dynamic gauge	SiRailScan - Basic configuration - Batch rail extraction - Semi-auto Rail extraction - Batch Catenary detection - Batch Clearance Static Gauge - Batch Tunnel Deformation - Batch Clearance Dynamic Gauge ATrack - Basic configuration - Driving dynamics - Trackplan - Railway calculation



SiRail-Suite

Standard Software Packages - Current Features

配套软件包 – 现有功能

SiRailSuite后处理软件

创新的软件解决方案，提高管理人员对铁路网络的监控管理，具有变形分析和计算功能。

SiRailSuite Essential(Plus)

The innovative software solutions contribute for the improvement in monitoring and control of the railway network conditions, for deformation analysis as well as for volume calculations.




ATrack

The Software solution created for track reverse engineering and optimization of algorithms, for railway design and planning, for as-built track geometry recovery and comparison between the designed and as-built track alignment.


ATrack后处理软件

轨道逆向工程与算法优化软件，具有铁路设计、计划，轨道几何要素计算等功能。




SiRail-Suite

SiRailSuite Essential(Plus) - Current Features SiRailSuite后处理软件 高级版 现有功能





- Batch - tunnel deformation analysis
- Automated calculation of differences “designed to as-built structure”
- Batch - automated extraction and adjustment of the as-built rails

- 批量处理：隧道变形分析
- 自动计算：设计与竣工差值
- 批量处理：提取轨道线



SiRailSuite Essential(Plus) - Current Features – Collision Test/Clearance Analysis 后处理软件 高级版 – 现有功能 – 侵界检测、净空分析

- Definition of 2D Profile (for example import of *.DXF or *.XML-Safeload) • 定义二维断面、剖面（DXF或XML格式）
- Definition of 3D-Body (customized wagon profile) with 3 more parameters • 定义三维车体（基于下面三个参数）
 - (1) Distance between basepoints of the wheel 1. 轮体基准点间距
 - (2) Distance between the axis of the wheels 2. 轮体轴线间距
 - (3) Length of the wagon 3. 车厢长度



SiRailSuite Essential(Plus) - Current Features – Collision Test/Clearance Analysis
后处理软件 高级版 – 现有功能 – 侵界检测、净空分析

- **3D-Collision-Test:** Detection of problem-areas, also Collison-Test to designed Track-Geometry
- 三维侵界检测：基于设计轨道，检测侵界区域

Batch

Window

About

Resynchronize

Transform Scans (2 Rails)

Station Resynchronize


Rail Adjustment

Collision Test


Collision Test 2

3D-analysis of point-cloud to detect collision-points

3D-analysis of point-cloud to detect collision-points (also to designed alignment, additional PDF-Output)



lfd. Nr.	KM-Station [m]	Points	Max. Einragung [m]	Lichtraumprofil
	105221.32	16	0.008	BVG-U-Bahn Großlichtraum - Bahnsteig
	105221.32	880	0.003	BVG-U-Bahn Großlichtraum - Bahnsteig
	105233.51	19	0.009	BVG-U-Bahn Großlichtraum - Bahnsteig
	105233.51	179	0.002	BVG-U-Bahn Großlichtraum - Bahnsteig
1	105416.90	1450	0,009	BVG-U-Bahn Großlichtraum - Bahnsteig
2	105424.90	1823	0,012	BVG-U-Bahn Großlichtraum - Bahnsteig
3	105430.89	2323	0,014	BVG-U-Bahn Großlichtraum - Bahnsteig



Chainage: 105.8+ 4.054

Track gauge[m]: 1.460

Cant[m]: 0.054

Radius[m]: 488.137

X [m]: 22650.425

Y [m]: 18447.607

SiRail-Suite

SiRailSuite Essential(Plus) - Current Features – Collision Test/Clearance Analysis

后处理软件 高级版 – 现有功能 – 侵界检测、净空分析

- **2D Clearance-analysis (static, dynamic):** Exact determination of clearance infringements
- Based on European rules and individual Formulas (for example for SNCF - National French Railway Company)
- Calculation of potential clashes also between neighborhood tracks
- 二维净空分析（静态、动态）：准确检测净空值
- 基于欧洲规定（比如法国国家铁路公司）
- 计算潜在的临近轨道发生的碰撞

Batch Window About

Resynchronize

Transform Scans (2 Rails)

Station Resynchronize

Rail Adjustment

Collision Test

Collision Test 2

Scans Segmentation

Electric Wires Detection

Extract Rails

Switch Points

Scans Coloring

2D Dynamic Clearance

2D approximate collision analysis

Clearance options

EN15273 Clearance (Red)

EN15273 Min-Clearance (Yellow)

EN15273 Absolute Clearance (Green)

EN15273 Frame (Blue)

Contour N (SNCF)

Contour N majeure(SNCF)

Contour N (SNCF) Top Frame

Contour N majeure(SNCF) Top Frame

Speed: 60 Mv

Safety Buffer[m]: 0

Absolute terms

Chainage: 145.10719

0 36285 Punkte 301

Start[m]: -1 End[m]: 1

Fix Collision test Close

Ctrl + Shift + left mouse button to set Station

Absolute Terms

Speed: <= 80 km/h

k = 1.2

Tosc = 0.065 m.

Tvoie = 0.025 m.

Supl = 0 m.

T_D = 0.015 m.

I = 1.435 m.

h = 3.25 m.

L = 1.5 m.

SD = 0.4 m.

DO = 0.05 m.

h_{CO} = 0.5 m.

IO = 0.05 m.

Tsusp = 0.23 grad

h_P = 0 m.

Tcharge = 0.77 grad

Save OK

2D-Dynamic-Clearance (SNCF-developement from SiRailView), Excel-Table and DXF-Output


2D-Static-Clearance (ETS-Customer Italy), also calculation to neighbourhood track, Excel- and DXF-Output

SiRail-Suite

ATrack - Current Features

ATrack软件 现有功能

- **ATrack-Basic-Configuration:** Exact and automated determination of Track-Geometry (position, height)
- **ATrack-Railway-Calculation:** Railway-switches, single-points on the track, **Tamping-Machine-Export**
- **ATrack-Driving-Dynamics:** Calculation of possible speed along the track
- **ATrack-Track-Plan:** Final Product with result Track-Geometry
- ATrack基础配置: 准确、自动的检测轨道几何元素, 平面位置、高程
- ATrack铁路计算: 轨道道岔、捣固机单点导出
- ATrack动态分析: 计算列车行驶速度
- ATrack轨道计划: 轨道几何结果报告



Trasse : High-Speed

DRIVING DYNAMICS TRACK: ANALYZED SPEED 200km/h


Route: SBW-ADM NB

Area:

Track:

Processor:

Advice	El.Nr.	Station	Form	ve	max v	km/h	cf-pos.	dcf	Track-elements
restriction				u/lu	Ruck		ve o.		R1 c1 length
maximum Speed				speed	Comf./Sit.				
	1	108.1+	95.00	SLINE	200		130	0	0 1449.9
	2	109.6+	44.85	CLOTH	200	200.5	130	0	0 65.0
	3	109.7+	9.85	ARC	200	237.6	130	-3917	40 138.4
	4	109.8+	48.28	CLOTH	200	200.5	130	-3917	40 65.0
	5	109.9+	13.28	SLINE	200		130	0	0 1412.1




SiRail-Suite


New features 新功能

- Native Support of Pegasus Data (hpc) in SiRailSuite
- Leica Safeload-Integration in SiRailSuite
- 原生支持Pegasus产品点云数据
- 集成徕卡安全加密系统

"High-Wide" Laser Measurement and Documentation System





- Specific new clearance-calculations, dependent on guidelines of railway-operators
- Individual templates for specific customers
- Automated platform detection in SiRailSuite
- 新的净空计算方法，基于铁路操作标准
- 为特定客户定制成果模板
- 自动轨面检测



SiRail-Suite

New features 新功能

- Improvement of electric wire detection (precise detection of crossing wires above tracks)
- Classification of objects → Reduced processing time for calculations
- 提高接触网电力线检测准确性（精确检测交叉的电力线）
- 点云分类功能 -> 减少数据处理分析的时间



SiRail-Suite

New features 新功能

- Significant reducing of processing time in SiRail-Software
 - Processing speed benchmark*:
- 显著减少数据处理用时
 - 处理速度评分:

Feature Name 处理项目	SiRail 2018.1 [minutes 分钟]	SiRail 2018.2 [minutes 分钟]	Reduction 速度提升
Rails extraction 提取轨道线	32	7.5	4 times faster 4倍
Catenary wires extraction 提取接触网电力线	56	4	14 times faster 14倍
Cross-sections 提取断面	41	6	7 times faster 7倍
2d Clearance 净空分析	157	8	20 times faster 20倍
DTM (on trackbed)	107	< 1	😊

*Time measured on a 3 km tunnel dataset and processed on a quad-core laptop.





*测试条件：3公里隧道数据，搭载四核处理器的笔记本电脑。



SiRail-Suite

New Features 新功能

- Integration of ActiveX Plugin from ATrack (curvature-calculations, element-finding) into SiRailSuite Essential
- ATrack软件的曲线计算功能现在作为ActiveX插件集成到SiRailSuite Essential软件中了



SiRail-Suite

Current developments 发展现状

- Calculation of Maximum Clearance Profile along a planned track
- Clearance-Analysis of every desired 3D-Object – example picture: wind blades transport north america
- 计算沿线最大净空值
- 计算需要的三维物体的净空分析, 图片为北美风扇叶片运输







HEXAGON